



Gellite Range Electrical Specifications & Dimensions

Battery Model	Nom. Voltage (V)	Capacity C20 1.75VPC @ 20°C	Capacity C100 1.75VPC @ 20°C	Short Circuit Amps	Internal Resistance Milli-ohms	Terminal Type	Battery Weight (kg/lb)		Outline Dimensions (mm/inch)					
									Length		Width		Height	
GL-1218	12	18	19.5	643	14.4	F-M5	5.7	12.2	181	7.13	76	2.99	167	6.57
GL-1220	12	20	22	834	12.5	F-M5	6.3	13.5	181	7.13	76	2.99	167	6.57
GL-1226	12	26	28	1206	11.5	F-M5	8.3	17.9	166	6.54	175	6.89	126	4.96
GL-1228	12	28	30	1219	11.1	F-M5	8.5	18.3	166	6.54	175	6.89	126	4.96
GL-1235	12	35	38	1530	9.6	F-M6	10.8	23.4	195	7.68	130	5.12	154	6.06
GL-1240	12	40	43	1734	8.5	F-M6	13.5	29.3	197	7.76	165	6.5	172	6.78
GL-1250	12	50	55	1785	7.2	F-M6	14.5	31.3	197	7.76	165	6.5	172	6.78
GL-1255	12	55	60	1836	6.7	F-M6	17.0	36.8	230	9.06	137	5.39	210	8.27
GL-1260	12	60	65	1938	6.3	F-M6	20.0	43.4	350	13.8	168	6.62	178	7.01
GL-1270	12	70	76	2040	5.8	F-M6	21.5	46.7	350	13.8	168	6.62	178	7.01
GL-1280	12	80	86	2142	5.4	F-M6	22.5	48.9	259	10.2	168	6.62	215	8.5
GL-1290	12	90	98	2448	5.0	F-M6	23.0	50.0	259	10.2	168	6.62	215	8.5
GL-12100	12	100	108	2703	4.1	F-M6	27.0	58.8	305	12	168	6.62	215	8.5
GL-12110	12	110	120	2958	3.8	F-M6	29.5	64.3	305	12	168	6.62	215	8.5
GL-12120	12	120	130	3060	3.4	F-M8	31.5	68.7	332	13.1	174	6.86	220	8.67
GL-12135	12	135	146	3366	3.0	F-M8	36.5	79.1	408	16.1	175	6.9	210	8.27
GL-12150	12	150	162	3825	2.7	F-M8	42.0	91.2	340	13.4	173	6.81	288	11.3
GL-12165	12	165	178	4284	2.6	F-M8	45.0	97.8	480	18.9	170	6.7	240	9.45
GL-12180	12	180	195	4794	2.5	F-M8	50.0	108.8	530	20.9	210	8.27	220	8.67
GL-12200	12	200	216	5508	2.5	F-M8	56.0	122.0	530	20.9	210	8.27	220	8.67
GL-12230	12	230	250	5508	2.4	F-M8	62.0	135.2	520	20.5	238	9.37	220	8.67
GL-12250	12	250	270	6018	2.2	F-M8	62.5	136.3	520	20.5	269	10.6	210	8.27
GL-12280	12	280	302	6222	2.1	F-M8	69.5	151.7	520	20.5	269	10.6	225	8.86
GL-12300	12	300	325	6426	1.9	F-M8	75.0	163.8	520	20.5	269	10.6	225	8.86
GL-675	6	75	81	1836	4.0	F-M6	11.3	23.7	185	7.3	112	4.39	205	8.06
GL-6135	6	135	146	3264	3.7	F-M6	17.0	36.2	195	7.68	170	6.69	210	8.27
GL-6165	6	165	180	4590	3.4	F-M8	24.5	52.7	260	10.2	180	7.09	252	9.92
GL-6200	6	200	216	4896	3.2	F-M8	28.0	60.4	306	12	168	6.61	225	8.86
GL-6230	6	230	250	5100	2.6	F-M8	32.0	69.2	322	12.7	178	7.01	230	9.06
GL-6240	6	240	260	5324	2.4	F-M8	34.0	73.6	243	9.57	188	7.40	275	10.8
GL-6250	6	250	270	5712	2.3	F-M8	34.5	74.7	322	12.7	178	7.01	230	9.06
GL-6300	6	300	325	6120	2.1	F-M8	47.0	102.2	295	11.6	178	7.01	345	13.6
GL-6330	6	330	356	6732	1.9	F-M8	48.0	104.4	295	11.6	178	7.01	345	13.6
GL-6400	6	400	432	8160	1.6	F-M8	56.0	122.0	295	11.6	180	7.09	426	16.8